



## **GHOST MOUNT INSTALLATION**

Flagpole, Grill-Post, Removable Handle

---

Ghost Mounts are used to accept LilliPad Marine's Ghost Mount Accessories; including: LilliPad Diving Board, Grill Post, Flagpole, Removable Ladder Handle and more. The following instructions are intended for use with single-Ghost Mount accessory mounting.

---

### **TOOLS REQUIRED:**

- Drill
  - 5/8" Drill Bit (Clean and Sharp)
  - 7/8" Wrench or Socket
  - Pen
- 



**VIDEO TUTORIALS**

**QUESTIONS**

800-279-3419

## INSTALLATION PROCEDURE:



1. If needed, gain access to the underside of the boat in your proposed mounting location. *(Remove or lower splash pans or drill a 2 1/2" access hole.)*



2. Place the accessory (mounting post or handle) in your proposed mounting location and confirm the following:

- The mounting hole is NOT over a cross-member or any other below deck intrusions such as wiring.
- The mounting location clears the cross-members enough to allow for proper placement of the stamped retaining washer on the bottom side of the flooring surface



3. Once placement is confirmed, lightly mark the mounting location on the flooring surface.



4. Using a very sharp drill bit, drill a 5/8" hole, straight-down, in the mounting location. Clean up woodchips, above and below deck, to ensure a smooth surface both above and below deck to ensure a clean path for the mounting body.



5. Push the Ghost Mount body into the mounting location. (If your mounting location is close to a cross-member, confirm the proper positioning of the "flats" on the mounting body in relation to the stamped retaining washer that will be placed on the bottom side.)



6. Install the stamped retaining washer (teeth facing up and into the plywood) followed by the flat washer, lock washer, and nut. Tighten the nut to 20 ft/lbs. using a 7/8" wrench or socket.

**IMPORTANT:** DO NOT use power tools to tighten.